



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet PULITEX



Safety Data Sheet dated 28/11/2011, version 3.6

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Mixture identification:
Trade name: PULITEX
Trade code: 12710/04

1.2. Relevant identified uses of the substance/mixture and uses advised against

Recommended use:

Degreaser detergent for mechanical parts (aerosol)

1.3. Details of the supplier of the safety data sheet

Company:

SILICONI COMMERCIALE SPA - Via Francia 4 Z.I. 36053 Gambellara (VI) ITALY tel n. +39 0444 649766

Competent person responsible for the safety data sheet:

info@siliconi.it

1.4. Emergency telephone number

SILICONI COMMERCIALE SPA - ph n. +39 0444 649766

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Directive criteria, 67/548/CE, 99/45/EC and following amendments thereof:

Properties / Symbols:

F+ Extremely flammable

R Phrases:

R12 Extremely flammable.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements



F+

Symbols:

F+ Extremely flammable

R Phrases:

R12 Extremely flammable.

S Phrases:

S2 Keep out of reach of children.

S23 Do not breathe aerosols.

S51 Use only in well-ventilated areas.

Special Provisions:

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Avoid to inhale directly and to spray into for eyes

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Keep out of reach of children. For professional use only.

The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

PULITEX

25% - 30% Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen

Index number: 649-327-00-6, CAS: 64742-48-9, EC: 265-150-3

Xn; R65



3.10/1 Asp. Tox. 1 H304

P Note

25% - 30% Hydrocarbons, C3-4; Petroleum gas

Index number: 649-199-00-1, CAS: 68476-40-4, EC: 270-681-9

F+; R12; substance with a Community workplace exposure limit



2.5 Press. Gas H280



2.2/1 Flam. Gas 1 H220

K Note

12.5% - 15% Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen

CAS: 64771-72-8, EC: 265-233-4

Xn; R65



3.10/1 Asp. Tox. 1 H304

1% - 3% 1,2-dichloropropane; propylene dichloride

Index number: 602-020-00-0, CAS: 78-87-5, EC: 201-152-2

F,Xn; R11-20/22



2.6/2 Flam. Liq. 2 H225



3.1/4/Oral Acute Tox. 4 H302



3.1/4/Inhal Acute Tox. 4 H332

For the wording of the listed risk phrases refer to section 16

4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

N.A. as aerosol preparation.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

None

5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for fire-fighters

Use suitable breathing apparatus .



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

PULITEX

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

- 6.1. Personal precautions, protective equipment and emergency procedures
Wear personal protection equipment.
Remove all sources of ignition.
Remove persons to safety.
See protective measures under point 7 and 8.
- 6.2. Environmental precautions
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
Wash with plenty of water.
- 6.4. Reference to other sections
See also section 8 and 13

7. HANDLING AND STORAGE

- 7.1. Precautions for safe handling
Pressurized container. Do not perforate or burn even after use.
Do not use near fire or other possible sources of ignition. During work phase do not smoke.
Avoid contact with skin and eyes, inhalation of vapours and mists.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
- 7.3. Specific end use(s)
None in particular

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1. Control parameters
Hydrocarbons, C3-4; Petroleum gas - CAS: 68476-40-4
TLV TWA: 1000 ppm
1,2-dichloropropane; propylene dichloride - CAS: 78-87-5
TLV TWA: ppm 75 A4
TLV STEL: ppm 110 A4
- DNEL Exposure Limit Values
N.A.
- PNEC Exposure Limit Values
N.A.
- 8.2. Exposure controls
- Eye protection:
Wear goggles with lateral protection EN166 .
If exposure to vapours cause a sense of bother to eyes, use antigas mask with complete facial.
- Protection for skin:
It is not necessary in case of brief contact except for wearing antistatic clean and covering garments.
In case of long and frequent contact use protective and waterproof garments to this material.
Choosing specific protection as peak, gloves, boots, overalls depends on the type of operations.
- Protection for hands:
During normal manipulation it is not necessary a particular protection.
In case of frequent contacts protect hands with gloves resistant to solvents (OVC, PE, neoprene, not natural rubber).
- Respiratory protection:
The levels of air concentration should be maintained under the exposure limits. If inhalation are over exposure limit use a supplied air respirator with cartridge filter. Filter type EN 141.



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

PULITEX

Thermal Hazards:

The aerosol container if overheated, deforms, breaks and it can be thrown a considerable distance

Environmental exposure controls:

Keep the container and use the product only in well ventilated place. A located ventilation may be necessary for some operations.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance and colour:	Contenitore a pressione con base e gas liquefatti
Odour:	caratteristico
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	N.A.
Initial boiling point and boiling range:	N.A.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	2
Flash point:	< 0 °C
Evaporation rate:	N.A.
Vapour pressure:	3-5 bar
Relative density:	N.A.
Solubility in water:	insolubile
Lipid solubility:	si
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	> 400°C
Decomposition temperature:	N.A.
Viscosity:	N.A.
Explosive properties:	N.A.
Oxidizing properties:	N.A.

9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

10. STABILITY AND REACTIVITY

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Keep away from sunlight, overheating. Keep at temperature not exceeding 50°C. Keep away from oxidant agents

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen - CAS: 64742-48-9

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 5000 mg/m3 - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen - CAS: 64771-72-8

a) acute toxicity:



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

PULITEX

Test: LC50 - Route: Inhalation - Species: Rat > 5000 mg/m³ - Duration: 4h
Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg
1,2-dichloropropane; propylene dichloride - CAS: 78-87-5
LD50 Oral (RABBIT)>1900mg/Kg
LD50 Skin (RABBIT): 8750 mg/Kg
LC50 Inhal (RAT 8h):3000 ppm

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

12. ECOLOGICAL INFORMATION

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

It doesn't Contain CHLORINE-FLUORINE-CARBIDE.

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen - CAS: 64742-48-9

Test: EC50 - Species: Daphnia - Duration h: 48 - mg/l: 1000

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen - CAS: 64771-72-8

Test: EC50 - Species: Daphnia - Duration h: 48 - mg/l: 1000

12.2. Persistence and degradability

None

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Disposal should be in accordance with local, state or national legislation. Aerosol container can explode at temperature Above 50°C if contains little gas residue. Spray all the aerosol content before disposal.

The product has to be considered: special dangerous disposal.

Waste disposal key:

The aerosol as a domestic waste is excluded from the application of such a normative for industrial activity, the empty aerosol for professional use can be classified as follow: 15.01.10: packaging containing residues of dangerous substances or residues contaminated by these substances.

14. TRANSPORT INFORMATION

14.1. UN number

ADR-UN number: 1950

IATA-Un number: 1950

IMDG-Un number: 1950

14.2. UN proper shipping name

ADR-Shipping Name: AEROSOLS, Flammable Limited Quantity: max 1000ml Total gross mass of package not exceed 30 kg LQ2

IATA-Technical name: AEROSOLS, Flammable

IMDG-Technical name: AEROSOLS Limited Quantity: max 1000ml Total gross mass of package not exceed 30 kg LQ2



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

PULITEX

- 14.3. Transport hazard class(es)
ADR-Class: 2, 5F
ADR-Label: <UN1950 AEROSOLS>
IATA-Class: 2.1
IATA-Label: <UN1950 AEROSOLS>
IMDG-Class: 2
- 14.4. Packing Group
- 14.5. Environmental hazards
Marine pollutant: No
- 14.6. Special Precautions for User
IMDG-Technical name: AEROSOLS Limited Quantity: max 1000ml Total gross mass of package not exceed 30 kg LQ2
IMDG-EMS: F-D
IMDG-MFAG: S-U
- 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
N.A.

15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n. 1272/2008 (CLP), Regulation (CE) n. 790/2009 (1° ATP CLP), Regulation (EU) n. 453/2010 (Annex I).

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.
Regulation (EC) nr 648/2004 (detergents).
1999/13/EC (VOC directive)

15.2. Chemical Safety Assessment
No

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

R11 Highly flammable.
R12 Extremely flammable.
R20/22 Harmful by inhalation and if swallowed.
R65 Harmful: may cause lung damage if swallowed.

H304 May be fatal if swallowed and enters airways.
H280 Contains gas under pressure; may explode if heated.
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H332 Harmful if inhaled.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold
CCNL - Appendix 1

Insert further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended. This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS: Chemical Abstracts Service (division of the American Chemical Society).
CLP: Classification, Labeling, Packaging.
DNEL: Derived No Effect Level.



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

PULITEX

EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.